



USER GUIDE

Filling the Tornado-T Tank:

- 1. Remove the tank cartridge from the atomizer cone
- 2. Remove the end cap of the tank cartridge
- 3. Fill the tank cartridge, ensuring to leave a minimum of 1mm space at the top and reattach the end cap
- Push the tank cartridge firmly into the atomizer cone until you hear a click
- 5. Screw the atomizer cone onto the battery
- Before pressing the battery button take two sharp inhales and one gentle exhale on the mouthpiece of the tank cartridge
- Place the mouthpiece of the tank cartridge into your mouth, depress the battery button and inhale gently for three-five seconds, release the power button and exhale when ready.
- Refill your tank cartridge when the fluid level reaches approx 5mm in the viewing window when the device is inverted. Do not operate with an empty cartridge.

Battery Operation:

To turn the battery on or off click the power button 5 times within 2 seconds.

The Tornado battery has 2 modes of operation, regulated and unregulated power output. Regulated output produces a constant output of 3.7V from fully charged to discharged. Unregulated output produces a higher output of 4.2V which diminishes to 3.3V over the period of discharge.

To toggle between the 2 modes, turn the battery off by clicking the power button 5 times, once off hold the power button for approximately 5 seconds, the power button will flash white for regulated mode and orange for unregulated mode, press the power button 5 times to turn the battery back on in the mode selected.









Unregulated mode

Charging:

To charge the battery, connect the supplied USB cable to a suitable power source such as a computer or USB power adapter. The power button will light red until charging is complete when the light will go out to indicate charging is complete.

¥

Battery charge remaining:

The power button LED will show white if the charge remaining is 60% or more, the LED will change to pale blue when below 60% charged. The LED will turn to dark blue when there is 10% or less remaining charge. When fully discharged the LED will flash 20 times and shut down, the battery will require charging before further use. The Tornado T can be used normally whilst being charged.









100% to 60% charged

60% to 10% charged

Less than 10% charged

PRECAUTIONS

- Store the Tornado T e-cigarette and its accessories away from children whilst not in use.
- · Please only use the charging cable provided.
- Please dispose of dead batteries in accordance with your country's appropriate legislation.
- Do not charge the battery in a damp environment, in temperatures under 0°C or above 45°C.
- . Do not carry batteries in a pocket or bag with other metallic objects.

WARRANTY

The Tornado T components contained in each kit have a 28-day parts warranty. The USB cable supplied has a 12-month warranty. If any parts are found to be faulty within this time please contact our customer service team, and we will arrange for a replacement. We may require the goods to be returned for further investigation.

Manufactured in China under the authority of Pillbox38 UK Ltd, Stancliffe Street, Blackburn, Lancashire, BB2 2QR.

UK: Tel 01254 692244 www.totallywicked-eliquid.co.uk
USA: Tel 1(888) 761-9425 www.totallywicked-eliquid.com
GER: Tel 01803 942533 www.totallywicked-eliquid.de